



## **TECHNICAL SCHEME**





The technical scheme do not consider the dimensions of any postural and anti decubitus cushions.

SW: Considered external tube to external tube of the frame. The dimension between the internal faces of the side guards is + 10 mm than the SW.

**SD**: Considered external table to external table.

**CG**: Considered from the backrest foam to the axle of the rear wheels.

SHF and SHR: Seat height front and rear can be adjusted only by tilting the seat. The frame tubes height than the floor is fixed.

BRH: Considered from the seat (upholstery or carbon) to the top of the backrest tube.

For a right sizing of the wheelchair is recommended:

 $\bigcirc$  SW | Seat Width  $\_$  A space of  $\pm$  5 mm between the user basin and the side guards

(2) SD | Seat Depth  $_{-}$  A space of  $\pm$  50 mm between the user's popliteal fossa and the rigid carbon seat.

**SW:** 240 – 320 mm in increments of 20 mm

**SHF:** 380 – 450 mm in increments of 10 mm



**MAXIMUM USER WEIGHT:** 75 Kg **SD:** 280 - 360 mm in increments of 20 mm

**KHL:** 90 – 360 mm in increments of 10 mm

TOTAL WIDTH (TW) (Camber 0°) SW +175 mm (Camber 3°) SW + 220 mm **BRH:** 240 – 375 mm in increments of 15 mm

**CG:** 50 – 90 mm in increments of 20 mm

**TOTAL DEPTH (TD)** SD280, 300 and 320 = 730+50-CG SD340 and 360 = 770+50-CG **SHR:** 320 – 390 mm in increments of 10 mm

**BRA:** 85° - 95° in increments of 1°

**TRASPORT WEIGHT:** (Without rear wheels) ± 4.5 kg\*



## \* CONFIGURATION:

SW240 / SD280 / KHL280 / BRH240 / BRKASL / FRKDS2 / FRWHP4 / SDK / BKRTT



## STANDARD CONFIGURATION

2024 rev0

Frame type: Straight frame (FRMDR)
Seat width (SW): from 240 to 320 mm
Seat depth (SD): from 280 to 360 mm

Camber Rear Wheels (CRW): 0° or 3°

**Center of Gravity (CG):** from 50 to 90 mm

Frame color: Black (NR)

Graphite Grey (GG) Light Green (VO) Yellow (GO)

**Rear wheels axle:**Black matte painted aluminium (AXALKID)

**Type of seat:** Carbon fiber seat pan with tilting system (CARBTK)

**Seat height rear (SHR):** from 320 to 390mm from 380 to 450 mm

**Backrest system:** Folding backrest and adjustable angle (BKRUK) **Backrest type:** Aria® adjustable Tension Backrest (BKRTT)

**Backrest height (BRH):** from 240 to 375 mm **Backrest angle (BRA):** Angle from 85° to 95°

**Footrest:** Footrest with angle adjustable plate (FOOTK)

**Knee to heel length (KHL):** from 90 to 360 mm

**Brakes support:**Aluminium standard clamp (BRKASL2) **Brakes:**Aria® scissor lock (BRKASL + BRKASR)

**Rear wheels type:** 22 " Black Wheel with black hub and black spokes (RWHAG.2)

**Handrim 22":**Black anodized aluminium (HDRMB.2)

Silver anodized aluminium (HDRMS.2)

Tyre 22x1.00: Schwalbe Right Run - Black/Grey (WTSWR.2)

Forks: Aria® Double - Sided - black anodized aluminium (FRKDS2)

Front casters: 3" Black plastic (FRWHP3), 4" Black plastic (FRWHP4)

**Side guards / Armrests:**Black ABS Fendered (SDGKID)

Calf band: Calf band, height 8 cm - black textile (CLFB8)

Manufacturer's suggested retail price: 2500 €