

The technical scheme do not consider the dimensions of any postural and anti decubitus cushions.

SW: Considered external tube to external tube of the frame. The dimension between the internal faces of the side guards is +5mm than the SW.

SD: Considered the depth of the seat. It considers the dimension from the end of the seat to the back tube.

SL: Considered the length of the seat pan. SL with CARBTT2 = SD - 60mm | SL with CARBTS1 = SD | SL with CARBFS1 = SD

CG: Considered from the backrest tube to the axle of the rear wheels.

SHF and SHR: Seat height front and rear can be adjusted.

BRH: Considered from the seat (upholstery or carbon) to the top of the backrest tube.

For a right sizing of the wheelchair is recommended:

1 SW | Seat Width $_$ A space of \pm 5 mm between the user basin and the side guards

SD | Seat Depth _ A space of ± 50 mm between the user's popliteal fossa and the seat (rigid carbon or upholstery).



SW: 340 – 460 mm in increments of 20 mm



SD: 380 – 460 mm in increments of 20 mm



BRH: 270 – 405 mm in increments of 15 mm



SHR: 365 – 425 mm in increments of 15 mm



SHF: 435 – 495 mm in increments of 15 mm



KHL: 310 – 440 mm in increments of 10 mm



CG: 80 - 120 mm in increments of 20 mm



BRA: 87° - 93° in increments of 3°



CRW: 0° or 3°



FRM 83= 100 - 140 mm FRM93= 135 - 175 mm in increments of 20 mm



TOTAL WIDTH (TW) (Camber 0°) SW +175 mm (Camber 3°) SW + 220 mm



TOTAL DEPTH (TD) StF + SD + 105 + 100 + (100-CG)



TRASPORT WEIGHT: (Without rear wheels) \pm 6.0 kg*



MAXIMUM USER WEIGHT: 120 Kg



* CONFIGURATION:

SW340 / SD420 / STF120 / CG100 / BKRUR / BRH255 / FOADJ / BRKASL / FRKDS2 / BRKASL2 / ALCMT116 / FRWC4 / CARB24 / BKRTT3



STANDARD CONFIGURATION

Frame angle: Angle 83° - Closed frame (FRM83)

Angle 93° - Open frame (FRM93)

Seat width (SW):from 340 to 460 mmSeat depth (SD):from 360 to 460 mmSeat to footrest (STF):from 120 to 160 mm

Camber Rear Wheels (CRW): 0° or 3°

Center of Gravity (CG): from 80 to 120 mm

Frame color: Black (NR)

Graphite Grey (GG) Light Green (VO) Yellow (GO)

Seat type: Upholstery seat (CARBTT2)

Seat height rear (SHR): from 380 to 450 mm
Seat height front (SHF): from 480 to 520 mm
Backrest system: Fixed backrest (BKRUR)

Backrest: Aria® tension straps backrest (BKRTT3)

Backrest height (BRH): from 270 to 405 mm **Backrest angle (BRA):** 90° to floor (BRA90)

Footrest: Carbon fibre adjustable in height and flexion-extension (FOADJ)

Knee to heel length (KHL): from 340 to 430 mm

Brakes support:Aluminium standard clamp (BRKASL2) **Brakes:**Aria® scissor lock (BRKASL + BRKASR)

Rear wheels dimensions: 24 "

25 "

Rear wheels type:Black Wheel with black hub and black spokes (RWHAG)

Handrim 24" / 25":

Black anodized aluminium (HDRMB)

Silver anodized aluminium (HDRMS)

Tyre 24x1.00 / 25x1.00: Schwalbe Right Run - Black/Grey (WTSWR)

Forks: Aria® Double - Sided - black anodized aluminium (FRKDS2)

Front casters:

Black plastic 3" (FRWHP3)

Black plastic 4" (FRWHP4)

Side guards support:Aluminium support (ALCMT116) **Side guards:**Black ABS Fendered (SDAL3)

Calf band: Calf band, height 8 cm - black textile (CLFB8)

Manufacturer's suggested retail price:

scan to configure

